Classic Globe (GLS) 11W (75W) 2700K 1060Im E27 Dimmable Frosted Lamp

Partcode: ILGLSE27DC023 / Page: 1



As LED products produced using new technologies are used with old dimmer technology, achieving effective and smooth dimming can be challenging. For this dimmable lamp we have tested, and recommend, the dimmer detailed in the specification below.

This 11W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a cool white light and brightness, similar to a 75W filament bulb. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for living rooms, hallways and kitchens.

Product Details

Partcode: ILGLSE27DC023 Check Code: 210558 Range Name: Everyday Placement / Application: Indoor, General Lighting Product Type: GLS Warranty: 2 Years CE / RoHS: Yes

Physical Data

Lamp Base: E27 Base Type: Edison screw Base Colour: Matt white Globe Type: Classic Globe (GLS) Globe Finish: Frosted Material: Aluminium, Polycarbonate, Nickel plated brass Construction: Aluminium and Plastic heat-sink, Injection moulded diffuser

www.integral-led.com

integral LED

Partcode: ILGLSE27DC023 / Page: 2

Physical Data

Length: 125mm Width: 60mm Weight (Unpackaged Single Unit): 150g Lamp or Luminaire Shape: Round

Electrical Data

Voltage Range: 220-240V Power Consumption: 11.0 Watts Driver included: Yes Driver IC Manufacturer: Marvell Electric Current: AC Ampage: 64.00mA Frequency Range: 50 Hz Power Factor: >=0.50 Wattage Equivalent: 75 Watts Dimming: Dimmable with compatible dimmers Compatible Dimmer(s): Varilight JQP401W LVD Certified: Yes EN: EN-62560

Light Data

Lumens: 1,060lm Lumens per Watt: 96.0lm/W Beam Angle: 200° Correlated Colour Temperature (CCT): 2700k Colour Temperature: Warm Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) Instant on - Less than 1 second: Yes Lifetime: 15,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Partcode: ILGLSE27DC023 / Page: 3

Environmental



Energy Rating: A+ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788208570 Packaged Weight (Unit of 1): 190g Length (unit of 1): 140mm Width (unit of 1): 68mm Depth (unit of 1): 68mm **Outer packaging info available on website**

Product data last updated on: Wednesday, September 11, 2019 - 16:21

www.integral-led.com