

Classic Globe (GLS) 6W (40W) 2700K 470lm E27 Non-Dimmable Frosted Lamp

Partcode: ILGLSE27NC009 / Page: 1



This 6W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for low level light areas such as hallways, bedrooms, cupboards or where light is always on.

Product Details

Partcode: ILGLSE27NC009

Check Code: 500250

Range Name: Everyday

Placement / Application: Indoor, General Lighting

Product Type: GLS

Warranty: 2 Years

CE / RoHS: Yes

Physical Data

Lamp Base: E27

Base Type: Edison screw

Base Colour: Matt white

Globe Type: Classic Globe (GLS)

Globe Finish: Frosted

Material: Plastic, Polycarbonate, Nickel plated brass

Construction: Aluminium and Plastic heat-sink, Injection moulded diffuser

Partcode: ILGLSE27NC009 / Page: 2

Physical Data

Length: 110mm

Width: 60mm

Weight (Unpackaged Single Unit): 54g

Lamp or Luminaire Shape: Round

Electrical Data

Voltage Range: 220-240V

Power Consumption: 6.0 Watts

Driver included: Yes

Driver IC Manufacturer: Silergy

Electric Current: AC

Ampage: 63.00mA

Frequency Range: 50 Hz

Power Factor: ≥ 0.50

Wattage Equivalent: 40 Watts

Dimming: Non-dimmable

LVD Certified: Yes

EN: EN-62560

Light Data

Lumens: 470lm

Lumens per Watt: 78.0lm/W

Beam Angle: 240°

Correlated Colour Temperature (CCT): 2700k

Colour Temperature: Warm

Colour Rendering Index (CRI): ≥ 80

LED Type: Surface mounted device (SMD)

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs

Switching Cycles: $>7,500$ X

Partcode: ILGLSE27NC009 / Page: 3

Environmental

Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788208099

Packaged Weight (Unit of 1): 92g

Length (unit of 1): 123mm

Width (unit of 1): 68mm

Depth (unit of 1): 68mm

Outer packaging info available on website

Product data last updated on: Wednesday, August 28, 2019 - 11:05