# GLS BULB E27 806LM 8.8W 4000K NON-DIMM 240 BEAM FROSTED INTEGRAL

ILGLSE27NE152



This 8.8W great all-purpose retrofit Integral LED Classic Globe (GLS) delivers a daylight output equivalent to 60W, offering big energy savings over equivalent incandescent bulbs. With a 806 lumen output and frosted finish this lamp is ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

#### **Details**

Quick Order Code: Barcode: Category: Range Name: Product Type: Market Segment: Warranty (Years): CE RoHS: Physical Data	309434 5055788272335 Lamps Everyday GLS Commercial indoor, Residential indoor 2 Yes
Product Length (mm): Product Width (mm): Product Weight (g): Material: Base Term: Bulb Base: Construction: Globe Finish: Globe Type:	105 60 30 Aluminium, Plastic Edison screw E27 Aluminium and Plastic heat-sink, Injection moulded diffuser Frosted GLS
Bulb or Luminaire Shape: Placement / Application:	Round Indoor, General Lighting

#### **Electrical Data**

Power (W):	8.8
Power Consumption (W) :	8.8
Power Factor:	0.5
Wattage equivalent (W):	60


Amperage (mA):	55
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

## **Light Data**


Luminous Flux in Lumens (Im):	806
Luminous efficacy (Im/W):	92
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	240
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

### Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Previous Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



## Packaging



## Portal.integral-led.com

Package Weight (g): 55 Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Length (mm):	120
Package Width (mm):	65
Package Depth (mm):	65
Qty per euro pallet:	1440

## Portal.integral-led.com