

## GLASS GU10 BULB 400LM 3.6W 2700K NON-DIMM 36 BEAM INTEGRAL

ILGU10NC083



The glass body and cleverly engineered surface mounted LEDs of the Integral LED Glass GU10 range give them an attractive look that is very similar to traditional halogen lamps. These GU10 lamps will retrofit easily into existing fittings and provide significant energy savings and longer lifetime than the halogen lamps they are designed to replace.

## **Details**

Quick Order Code: 324099

**Barcode:** 5055788230595

Category:LampsRange Name:GlassProduct Type:GU10

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 54
Product Width (mm): 50
Product Weight (g): 50

Optic: Designed to give a Halogen look

Material:GlassBase Term:GU10Bulb Base:GU10

**Construction:** Glass body and "fly eye" diffuser lens

Globe Finish: Dichroic look
Bulb Fixing: Downlight
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting
Spot Type: SMD with "COB like effect"

#### **Electrical Data**

Power (W): 3.6
Power Consumption (W): 3.6
Power Factor: 0.4

Wattage equivalent (W): 50
Amperage (mA): 28

**Dimming:** Non-Dimmable

Driver IC Manufacturer:

Driver Included:

Electric Current:

True Wattage Eq (W):

SM7307

Yes

AC

50

**EN:** EN-62560

LVD Certified: Yes

# **Light Data**

Luminous Flux in Lumens (Im): 390
Luminous efficacy (Im/W): 111
Peak Intensity (Cd): 800
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:36Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Surface mounted device (SMD)


Lifetime (hours): 15000
Switching Cycles: 7500
Useful Lumens (lm): 345

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A+ E **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





# **Packaging**

Package Weight (g): 53
Package Length (mm): 55
Package Width (mm): 55
Package Depth (mm): 60
Qty per euro pallet: 2800