

# 200W PRECISION PLUS 60° FLOODLIGHT 28000LM 4000K NON DIM IP66 IK08 5 YR WARRANTY

ILFLD320



The new high-performance and reliable Precision-Plus Floodlight range is robust, super bright and efficient with brightness levels from 13,000 to 26,000 lumens with up to 130lm/W efficacy. A discreet and sturdy aluminium die-cast housing with good heat dissipation, a toughened glass cover and an IP66 and IK08 rating, makes the floodlights perfect for outdoor industrial, commercial and facade lighting with 60° and asymmetric optics.

#### **Details**

Quick Order Code: 332709

Barcode: 5055788257639
Category: Luminaires
Range Name: Precision Plus

Product Body Finish: Black

Market Segment: Commercial & Industrial Outdoor

Warranty (Years): 5
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 432
Product Depth (mm): 60
Product Width (mm): 330
Product Weight (g): 5200

Material: Aluminium, Tempered Glass

**Construction:** Aluminium die-cast heat-sink, Tempered Glass

protective front cover, Integrated driver

Luminaire Fixing: Wall Mounted

Placement / Application: Indoor and outdoor, General lighting

#### **Electrical Data**

Power Consumption (W): 200
Power Factor: 0.9

**Dimming:** Non-Dimmable

Driver Included: Yes
Electric Current: AC

**EN:** EN-60598

LVD Certified: Yes

## **Light Data**

Luminous Flux in Lumens (Im): 28000 Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature Name: Cool White

Beam Angle:60Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Surface mounted device (SMD)


Lifetime (hours): 50000
Sensor / Overide: No
Switching Cycles: 25000

## **Environment**

**EN:** EN-60598

LVD Certified: Yes **CE RoHS:** Yes E **New Energy Rating: EU Luminaire:** L Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK08 IP Rating (Ingress Protection): IP65 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





## **Packaging**

Package Weight (g): 6000
Package Length (mm): 510
Package Width (mm): 430

Package Depth (mm): Portal.integ5al-led.com