Outdoor Luxstone 8.5WW 4000K 335Im IP54



The Integral LED Outdoor range offers style and substance, with contemporary designs and hardwearing, weatherproof aluminium construction. This range of modern luminaires creates the perfect accent lighting for exterior walls in residential and commercial environments with all the low-energy and long-life benefits of LED.

The LuxStone is an attractive up/down wall light with a polycarbonate diffuser that gives a gentle wash of light to your wall. The dark grey, powder coated finish is both beautiful and rugged.

Product Details

Partcode: ILDEA026 Check Code: 530208 Range Name: Wall Light Product Type: Outdoor Warranty: 3 Years CE / RoHS: Yes

Physical Data

Optic: Polycarbonate diffuser Material: Die cast aluminium body with powder coated finish

www.integral-led.com

Partcode: ILDEA026 / Page: 2

Physical Data

Length: 140mm Width: 88mm Depth: 45mm Weight (Unpackaged Single Unit): 370g Luminaire Fixing: Wall Mounted

Electrical Data

Voltage Range: 220-240V Power Consumption: 8.5 Watts Driver included: Yes Electric Current: AC Ampage: 350.00mA Frequency Range: 50/60 Hz Power Factor: >=0.40 Dimming: Non-dimmable LVD Certified: Yes EN: EN-60598

Light Data


Lumens: 335lm Lumens per Watt: 39.0lm/W Beam Angle: 50° Correlated Colour Temperature (CCT): 4000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Type: Chip-on-board (COB) Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Partcode: ILDEA026 / Page: 3

Environmental



Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 50 degrees IP (Ingress Protection) Rating: IP54 Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788233275 Packaged Weight (Unit of 1): 399g Length (unit of 1): 150mm Width (unit of 1): 92mm Depth (unit of 1): 52mm **Outer packaging info available on website**

Product data last updated on: Wednesday, September 11, 2019 - 17:02

www.integral-led.com