

100W PRECISION PLUS 60° FLOODLIGHT 14000LM 4000K NON DIM IP66 IK08 5 YR WARRANTY

ILFLD310



The new high-performance and reliable Precision-Plus Floodlight range is robust, super bright and efficient with brightness levels from 13,000 to 26,000 lumens with up to 130lm/W efficacy. A discreet and sturdy aluminium die-cast housing with good heat dissipation, a toughened glass cover and an IP66 and IK08 rating, makes the floodlights perfect for outdoor industrial, commercial and facade lighting with 60° and asymmetric optics.

Details

Quick Order Code: 713871

Barcode:5055788257592Category:LuminairesRange Name:Precision Plus

Product Body Finish: Black

Market Segment: Commercial & Industrial Outdoor

Warranty (Years): 5
CE RoHS: Yes

Physical Data

Product Length (mm): 355
Product Depth (mm): 55
Product Width (mm): 245
Product Weight (g): 3100

Material: Aluminium, Tempered Glass

Construction: Aluminium die-cast heat-sink, Tempered Glass

protective front cover, Integrated driver

Luminaire Fixing: Wall Mounted

Placement / Application: Indoor and outdoor, General lighting

Electrical Data

Power Consumption (W): 100
Power Factor: 0.9

Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

EN: EN-60598

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 14000 Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature Name: Cool White

Beam Angle:60Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 50000
Sensor / Overide: No
Switching Cycles: 25000

Environment

EN: EN-60598

LVD Certified: Yes **CE RoHS:** Yes E **New Energy Rating: EU Luminaire:** L Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK08 IP Rating (Ingress Protection): IP65 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g): 3600
Package Length (mm): 405
Package Width (mm): 305

Package Depth (mm): Portal.integral-led.com