# Downlight 11W (18W) 4000K 1000lm 150mm cut out Non-Dimmable Matt white finish

Partcode: ILDL150D006 / Page: 1



The new range of Integral Slim-line integrated downlights has been designed to achieve excellent lighting performance, with a smart, sleek design that looks good on or off.

The high luminous efficacy offers great saving in running cost when replacing old CFL downlights. The Polycarbonate diffuser gives uniform light over the entire lighting surface. The integrated driver and loop-in / loop-out connector means installation is quick and simple.

# **Product Details**

Partcode: ILDL150D006 Check Code: 430156 Range Name: Slimline Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: LED Downlights Warranty: 2 Years CE / RoHS: Yes

# **Physical Data**

Product Finish: Matt white Optic: Polycarbonate diffuser Material: Polycarbonate Construction: Injection moulding

# integral LED

# **Product Specification Sheet**

Partcode: ILDL150D006 / Page: 2

#### **Physical Data**

Depth: 31mm Diameter: 175mm Weight (Unpackaged Single Unit): 263g Cut Out Diameter: 150mm Luminaire Fixing: Recess mounted

#### **Electrical Data**

Voltage Range: 220-240V Power Consumption: 11.0 Watts Driver included: Integrated Electric Current: AC Frequency Range: 50/60 Hz Power Factor: >=0.90 Wattage Equivalent: 18 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-60598

#### **Light Data**


Lumens: 1,000lm Lumens per Watt: 91.0lm/W Lighting Method: Back-lit Beam Angle: 105° Correlated Colour Temperature (CCT): 4000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) LED Size: 2835 Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

# www.integral-led.com



Partcode: ILDL150D006 / Page: 3

#### **Environmental**



Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

### Packaging



EAN Barcode (unit of 1): 5055788222835 Packaged Weight (Unit of 1): 358g Length (unit of 1): 197mm Width (unit of 1): 197mm Depth (unit of 1): 57mm **Outer packaging info available on website** 

Product data last updated on: Wednesday, May 8, 2019 - 17:11