

ILGU10NC102



The Integral LED Classic GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

Details

Barcode: 5055788240976

Category: Lamps

Range Name: Classic

Product Type: GU10

Product Body Finish: Matt white

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2

CE RoHS: Yes

Physical Data

Product Length (mm): 54

Product Width (mm): 50

Product Weight (g): 25

Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded diffuser

Base Term: GU10

Bulb Base: GU10

Construction: Plastic White and "Classic look" difuser lens

Bulb Fixing: Downlight

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Spot Type: SMD with "COB like effect"

Electrical Data

Power (W): 4

Power Consumption (w): 4

Power Factor: 0.4

Voltage Range (v): 220-240

Wattage equivalent (W): 50

Amperage (mA): 34

Dimming: Non-Dimmable

Driver Included: Yes

Electric Current: AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (lm): 360

Luminous efficacy (lm/W): 90

Lumens Range: 250 to 470

Peak Intensity (Cd): 700

Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name: Warm

Beam Angle: 36

Colour Rendering Index (CRI): 80

Frequency Range (Hz): 50/60

Instant on (Less than 1 second): Yes

LED Type: Surface mounted device (SMD)

Lifetime (hours): 15000

Switching Cycles: 7500

Useful Lumens (lm): 345

Environment

EN: EN-62560

LVD Certified: Yes


CE RoHS: Yes

Energy Rating: A++

Hg 0% (Mercury Free): Yes

Lowest Operating Temperature (°C): -20

Maximum Operating Temperature (°C): 40



Packaging

Portal.integral-led.com

Package Weight (g): 50

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Length (mm): 55

Package Width (mm): 55

Package Depth (mm): 60

Portal.integral-led.com

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE