

SUPER SLIM 2 FLOODLIGHT IP67 1000LM 10W TUYA 3000/4000/6500K 120° DIMMABLE 100LM/W BLACK INTEGRAL

ILFLC245



This small and compact fitting is rated at IP67 and perfect for indoor and outdoor applications. It is highly efficient and durable making it a popular choice for long life applications. It utilises branded drivers and chips and it is fully guaranteed for 5 years.

Details

Quick Order Code: 606710

Barcode:5055788263494Category:LuminairesRange Name:Super Slim 2

Product Body Finish: Black

Market Segment: Residential and Commercial

Warranty (Years): 5
CE RoHS: Yes

Physical Data

Product Length (mm): 148
Product Depth (mm): 29
Product Width (mm): 129
Product Weight (g): 385

Material: Aluminium, Tempered Glass

Construction: Aluminium die-cast heat-sink, Tempered Glass

protective front cover, Integrated driver

Bulb or Luminaire Shape: Rectangle Luminaire Fixing: Wall Mounted

Placement / Application: Indoor and outdoor, General lighting

Electrical Data

Power Consumption (W): 10
Power Factor: 0.9

Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC
EN: EN-60598

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 1000

Correlated Colour Temperature (CCT) (K): 3000/4000/6500 CCT Switchable

Beam Angle:120Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 50000
Sensor / Overide: No
Switching Cycles: 25000

Environment

EN: EN-60598

LVD Certified: Yes **CE RoHS:** Yes F **New Energy Rating: EU Luminaire:** Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK08** IP67 IP Rating (Back/Recessed side): **IP Rating (Ingress Protection): IP67 Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g): 425
Package Length (mm): 155
Package Width (mm): 138

Package Depth (mm): Portal.int@gral-led.com